

DETAILS OF MODEL: FUSO CANTER 515 4 X 2 FEB21ER3SFBC AMT MWB MODEL.

The following specifications are standard equipment:

AXLE FRONT:	Independent front suspension. Capacity 2300kgs.
AXLE REAR:	Full floating banjo type, ratio 4.444:1. Capacity 3800kgs
BRAKES:	Hydraulic dual circuit Front and Rear Discs. Exhaust brake. ABS plus EBD (Electronic brake distribution) Transmission mounted park brake.
ACTIVE SAFETY:	Advanced Emergency Braking (AEBS) Lane Departure Warning System (LDWS) Electronic Stability Program (ESP)
CAB:	All steel manual tilt Cab, 4 point Hydro elastic mounts. ECE-R29 Approved. A/C. Heater / Demister. Side doors reinforced with impact beams, Laminated windscreen with tinted side and rear glass. Driver seat reclining with LH armrest and lumbar support. Intermittent wipers, washers on wiper blades. Dual Airbags & Seat Belt Pre-Tensioners, Electric Windows, Keyless central locking, 12V accessory outlet. External heated convex mirrors, Reverse beeper, 2 x cup holders. <i>Multi Media Package includes:</i> 7" LCD with touchscreen control, Bluetooth hands free phone calls, Bluetooth music streaming compatible, AM/FM Radio, Digital Radio, USB & 3.5mm Aux port and reverse camera compatible (1 camera included). Sat Navigation with Heavy Vehicle weight, length, height & haz mat selectable restrictions with 3yr free map updates.
CHASSIS:	Reinforced Tapered Channel low tare weight chassis. 750mm width. 440 MPa. Wheelbase 3400mm.
CLUTCH:	Dual clutch (wet multi plate) no clutch pedal in automated manual model.
ELECTRICAL:	Voltage 12V negative earth. Alternator 110 amp. 2 x 12 volt 70 Ah / 5hr batteries. Halogen 55W / 60W Headlamps.
ENGINE:	Fuso 4P10-T4 Variable Geometry Turbo Diesel (ADR80/03 Euro 5 & EEV) 4cyl DOHC, Air to Air Intercooled, Bosch Common Rail direct injection Diesel Particulate Filter (DPF) exhaust with in dash DPF display status. Colour dash display DPF Status with 0 – 9 (empty-full) Parked regeneration is possible from 7 – 9 bars. 110 Kw / 150 HP @2840-3500 rpm 370Nm torque @ 1350-2840 rpm. Flat torque curve.
FUEL:	Bosch common rail injection system, 100 litre fuel tank with lockable fuel cap.
STEERING:	Rack and pinion Power steering with telescopic / tilt adjustable steering column.
SUSPENSION FRONT:	Double Wishbone Front Independent Suspension with Coil Springs and Shock Absorbers.
SUSPENSION REAR:	Parabolic leaf with Shock Absorbers Rear Suspension.
TRANSMISSION:	6 speed overdrive Automated Manual transmission with Auto and Manual modes. Virtually instant gear changes. In dash gear lever with Park Brake Position.
WHEELS & TYRES:	7 x single piece disc rims, 15x5 wheels with 195/85R15 Tyres. 5 stud 208mm PCD.
SERVICING:	30,000kms Service intervals.
GVM / GCM:	GVM 4500kgs / GCM 8000kgs (Car License Suitability)

FIT OUT:

Bodywork

- 4.5m x 2.5m Steel Tray with Split Dropsides
- 3.5t Rated Towbar and 50mm Ball (Reece Type Hitch)

Electrical/Minespec

- High level LED S/T/I Lights to Headboard
- LED Beacon to Cabrack
- 97Db White Noise Reverse Alarm
- Hand Brake Alarm
- Whip Aerial on Cabrack
- 1kg Fire Ex in Cab
- 4.5Kg Fire Ex to Tray
- Battery Isolation Switch
- Headlights on kit
- 50/75 High Viz Tape to Tray and Cab
- 2 x Wheel Chocks to Chassis
- Wheel nut indicators
- Soft shell first aid kit
- Safety triangles
- 80Ch GME UHF & aerial

Miscellaneous

- Canvas seat covers, front and rear
- HD rubber floor mats – front & rear
- Darkest Legal Window Tint
- Reverse Camera